Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Shanghai Ogino Biotechnology
--------------------------------	------------------------------

Supplier's address: Nicole Wang, Einsteinstr. 2, Neuss 41464 Neuss Germany

Model identifier: WRGBII SLIM60

_	•			
IVna	Λt	light	source	٠.
IVDC	vı	HEILL	Jource	- •

Type of light source	::			
Lighting technology	used:	LED	Non-directional or directional:	NDLS
Light source cap-typ	e	External adapter		
(or other electric in	terface)	connection		
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable ligh	nt source:	No	Envelope:	-
High luminance ligh	t source:	No		
Anti-glare shield:		No	Dimmable:	Yes
		Product parar	neters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consumpti mode (kWh/1000 up to the nearest in	h), rounded	53	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		6 200 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode power (P _{on}), expressed in W		53,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,20
Networked standby for CLS, expressed rounded to the seco	in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
	ight	15	Spectral power	See image
	dth	584	distribution in the	in last page
without De	pth	128		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	19	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

