## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: EHEIM classicLED daylight

Supplier's address: Service, Plochinger Straße 54, 73779 Deizisau, DE

Model identifier: 4261011 - 550 mm

_	•		
Typa	Ot.	light	source:
IVDE	UI.	HEILL	source.

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type (or other electric interface)	24 V DC, ausziehbare Haltebügel, Kunststoffadapter für T5/T8					
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Only with specific dimmers			
Product parameters						
Parameter	Value	Parameter	Value			
	General product p	arameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	789 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode power (P <sub>on</sub> ), expressed in W	7,7	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	88			

			values that can be set			
Outer	Height	6	Spectral power	See image		
dimensions	Width	550	distribution in the	in last page		
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	33	range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-		
			Chromaticity	0,315		
			coordinates (x and y)	0,318		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		39	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)'-': not applicable; (b)'-': not applicable;

## **Spectral Power Distribution**

