Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

LED

Non-directional or

index, rounded to the nearest integer,

or the range of CRI-

NDLS

Supplier's name or trade mark: EHEIM classicLED daylight

Supplier's address: Service, Plochinger Straße 54, 73779 Deizisau, DE

Model identifier: 4265011 - 640 mm

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIGIIL	source.

Lighting technology used:

for CLS, expressed in W and

rounded to the second decimal

8			
		directional:	
Light source cap-type (or other electric interface)	24 V DC, ausziehbare		
(e. ease. electric interruce)	Haltebügel, Kunststoffadapter für T5/T8		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers
	Product parar	neters	
Parameter	Value	Parameter	Value
	General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	888 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode power (P _{on}), expressed in W	8,6	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net})	-	Colour rendering	88
	1	1	

			values that can be set			
Outer	Height	6	Spectral power	See image		
dimensions without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Width	640	distribution in the	in last page		
	Depth	33	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity	0,315		
			coordinates (x and y)	0,318		
Parameters for LED and OLED light sources:						
R9 colour rendering index value 39		39	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)_{'-'}: not applicable;

(b)_{'-'} : not applicable;

Spectral Power Distribution

