## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: EHEIM powerLED+ fresh daylight

Supplier's address: Service, Plochinger Straße 54, 73779 Deizisau, DE

Model identifier: 4252011 - 487 mm

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIKIIL	source.

Type of light source:							
Lighting technology used:	LED	Non-directional or directional:	NDLS				
Light source cap-type (or other electric interface)	24 V DC, ausziehbare Haltebügel, Kunststoffadapter für T5/T8						
Mains or non-mains:	NMLS	Connected light source (CLS):	No				
Colour-tuneable light source:	No	Envelope:	-				
High luminance light source:	No						
Anti-glare shield:	No	Dimmable:	Only with specific dimmers				
Product parameters							
Parameter	Value	Parameter	Value				
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	D				
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 040 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 200				
On-mode power (P <sub>on</sub> ), expressed in W	13,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	85				

			values that can be set				
Outer	Height	20	Spectral power	See image			
dimensions	Width	487	distribution in the	in last page			
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	60	range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-			
			Chromaticity	0,319			
			coordinates (x and y)	0,333			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		-	Survival factor	1,00			
the lumen maintenance factor		0,96					

(a)<sub>'-'</sub>: not applicable;

(b)<sub>'-'</sub> : not applicable;

## Spectral Power Distribution

