## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: EHEIM powerLED+ fresh plants

Supplier's address: Service, Plochinger Straße 54, 73779 Deizisau, DE

Model identifier: 4254021 - 771 mm

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	<b>3</b> Uui C	c.

Type of light source:						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	24 V DC,					
(or other electric interface)	ausziehbare					
	Haltebügel, Kunststoffadapter					
	für T5/T8					
Mains or non-mains:	NMLS	Connected light	No			
		source (CLS):				
Colour-tuneable light source:	Yes	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Only with			
			specific dimmers			
Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on-	28	Energy efficiency	F			
mode (kWh/1000 h), rounded up to the nearest integer		class				
Useful luminous flux (фuse),	2 425 in	Correlated colour	10 000			
indicating if it refers to the flux	Sphere (360°)	temperature,	10 000			
in a sphere (360°), in a wide	Spriere (See )	rounded to the				
cone (120º) or in a narrow cone		nearest 100 K,				
(90º)		or the range of				
		correlated colour				
		temperatures,				
		rounded to the nearest 100 K, that				
		can be set				
On-mode power (P <sub>on</sub> ),	24,8	Standby power (P <sub>sb</sub> ),	0,00			
expressed in W	,	expressed in W	,			
		and rounded to the				
		second decimal				
Networked standby power (P <sub>net</sub> )	-	Colour rendering	78			
for CLS, expressed in W and		index, rounded to				
rounded to the second decimal		the nearest integer,				
		or the range of CRI-				

			values that can be set			
Outer	Height	20	Spectral power	See image		
dimensions	Width	771	distribution in the	in last page		
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	60	range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-		
			Chromaticity	0,296		
			coordinates (x and y)	0,258		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		0	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)<sub>'-'</sub>: not applicable;

(b)<sub>'-'</sub> : not applicable;

## Spectral Power Distribution

